

# SUITABLE ACCESSORIES FOR YOUR WELLNESS PROJECT



Humidification, Dehumidification  
and Evaporative Cooling

 **condair**



~condair



## Index

Steam hoses	Page..... 2
Hoseclamps	Page..... 3
Insualtion hoses (EcoTherm)	Page ..... 4
Fragrance pump	Page ..... 5
Steam inlets	Page ..... 6
Fans	Page..... 7
Regulator and Temperature sensors	Page..... 7
Steambath control and displays	Page ..... 8- 9
Mounting sleeves and spotss	Page ...10- 11
LED Controller	Page ..... 12
Push-button plates	Page ..... 13
Mounting material	Page ...14- 15
Water treatment	Page ...16- 17

## Steamhoses




### Features of our steamhoses:

- High side pressure stability
- Odourless
- Hygienic
- Inner layer as per NSF61 (drinking water)
- Outer layer as per UL94V0 (flame resistant)
- Operating temperature-25°C to 105°C



Capacity kg/h	Omega Pro	Omega	AT4D	Sigma
<b>2</b>	—	DS60	—	—
<b>4</b>	—	DS60	—	DS22
<b>5</b>	DS80	—	DS22	DS22
<b>6</b>	—	DS60	—	—
<b>8</b>	DS80	DS60	DS22	DS22
<b>10</b>	DS80	—	—	—
<b>12</b>	—	DS80	—	—
<b>15</b>	—	—	DS35	DS35
<b>16</b>	DS80	DS80	—	—
<b>20</b>	DS80	DS80	—	—
<b>23</b>	—	—	DS35	DS35
<b>24</b>	DS80	—	—	—
<b>30</b>	DS80	—	—	—
<b>32</b>	—	—	DS35	DS35
<b>40</b>	DS80	—	—	—
<b>45</b>	—	—	2 x DS35	2 x DS35
<b>65</b>	—	—	2 x DS35	2 x DS35

## Hoseclamps for steamhoses



Construction of steam hose (cross section)

Art.-No.	Type	Inner-diameter D2	Outer-diameter D1	Roll length	Order information
2586148	DS22	22.0 mm	31.0 mm	20 m	Complete roll only
2586142*				100 m	By the meter, up to 19 m
2586149	DS60	29.5 mm	40.0 mm	20 m	Complete roll only
2586144*				100 m	By the meter, up to 19 m
2586150	DS35	35.0 mm	46.0 mm	20 m	Complete roll only
2586145*				80 m	By the meter, up to 19 m
2586152	DS80	43.5 mm	55.5 mm	20 m	Complete roll only
2586147*				60 m	By the meter, up to 19 m



### Matching hoseclamp to DS22

Art.-No. 1100432: Includes 2 pcs. of hoseclamps

### Matching hoseclamp to DS60

Art.-No. 2591276: Includes 2 pcs. of hoseclamps

### Matching hoseclamp to DS35

Art.-No. 2539583: Includes 2 pcs. of hoseclamps

Art.-No. 2539584: Includes 10 pcs. of hoseclamps

### Matching hoseclamp to DS80

Art.-No. 2538898: Includes 2 pcs. of hoseclamps

Art.-No. 2538899: Includes 10 pcs. of hoseclamps


## Insulation hose EcoTherm



### Good to know:

The insulation hose forms an air cushion around the steam hose and thus has a heat-insulating function, which reduces the formation of condensation in the steam hose. Therefore, in addition to the insulation hose, an O-ring is required for sealing.

### Operating temperature -40°C to 125°C



Art.-No.	Type	Inner-Ø D2	Outer-Ø D1	Roll length	Order information
2538838	EcoTherm22	40 mm	49 mm	20 m	By the meter, up to 19 m
2538839	EcoTherm60	55 mm	64 mm	20 m	By the meter, up to 19 m
2538840	EcoTherm80	70 mm	80 mm	20 m	By the meter, up to 19 m

\*Specify desired length when ordering

### Which insulation hose (EcoTherm) fits to which steam hose (DS)?

#### EcoTherm22 to DS22

Art.-No. 2538838  
Includes: Sold by the meter until 19m\*

Art.-No. 2538900  
Includes: 2 pcs. O-rings to Eco Therm 22

Art.-No. 2538901  
Includes: 10 pcs. O-rings to EcoTherm 22

#### EcoTherm60 to DS35

Art.-No. 2538839  
Includes: Sold by the meter until 19m\*

Art.-No. 2539585  
Includes: 2 pcs. O-rings to Eco Therm 60

Art.-No. 2539586  
Includes: 10 pcs. O-rings to EcoTherm 60

#### EcoTherm60 to DS60

Art.-No. 2538839  
Includes: Sold by the meter until 19m\*

Art.-No. 2538902  
Includes: 2 pcs. O-rings to Eco Therm 60

Art.-No. 2538903  
Includes: 10 pcs. O-rings to EcoTherm 60

#### EcoTherm80 to DS80

Art.-No. 2538840  
Includes: Sold by the meter until 19m\*

Art.-No. 2538908  
Includes: 2 pcs. O-rings to Eco Therm 80

Art.-No. 2538909  
Includes: 10 pcs. O-rings to EcoTherm 80

## Accessoires fragrance injection



### Fragrance dosing pump

Art.-No. 2560460: 230VAC Fragrance dosing pump



### Hose silicone

Art.-No. 2591502 : Hose silicone Ø 6/4 per Meter



### Suction hose

Art.-No. 2568956



### Injector

Art.-No. 2400529: Injector fragrance Ø 22 mm  
Art.-No. 2591270: Injector fragrance Ø 30 mm  
Art.-No. 2400530: Injector fragrance Ø 35 mm  
Art.-No. 2591269: Injector fragrance Ø 45 mm



### Assembly station

At the practical assembly station, the filter cartridge and the perfume pump can be attached and the perfume container safely parked.

Dimensions: W 402 mm, H 600 mm, D 193 mm  
Art.-No. 2591019

### Replacement cartridge:

Art.-No. 2590308: Filter cartridge S  
Art.-No. 2590309: Filter cartridge L  
Art.-No. 2591018: Filter head

## Steam inlet



**DDS22 Steam bath nozzle**  
Small steam bath nozzle for  
max. 4kg/h capacity  
For steam hose DS22 with  
Ø22 mm  
Art.-No. 2402732

**Steam nozzle set W22**  
fits with steam hose DS22 Ø 22 mm, Art.-No. 2560985

**Steam nozzle set W30**  
fits with steam hose DS60 Ø30 mm, Art.-No. 1119246

**Steam nozzle set W35**  
fits with steam hose DS35 Ø35 mm, Art.-No. 2560986



**Steam nozzle set W45**  
fits with steam hose DS80 Ø45 mm, Art.-No. 1119247

**High quality steel steam outlet element**  
for use with steam nozzle set  
W22/W30,  
Art.-No. 2591790

**Steam Inlet**  
Steam inlet for the mixing and inserting of steam and fresh  
air into the steam room. For a dense steam appearance and  
a lower temperature of the inserted steam:

- Mixing tube made of stainless steel V4A with  
connections for fresh air and steam
- Diameter 110 mm, Installation length 280 mm
- Cover made of stainless steel V4A 140 x 140 mm with  
fixation screws
- Thread for steam hose 1"

Dimensions:  
Ø110 mm, installation length 280 mm  
Cover 140 x 140 x 22,5 mm with fixing screws and  
mounting flange. Art.-No. 2591794



## Fans and regulator



### Fan

Special 3-stage insertion tube fan for Ø 150 mm.  
Nom. Voltage: 24V 1~50/6Hz  
Current draw: 2.25/2.20A  
Power consumption:  
40 Watt. Speed / min-1  
2760/3200  
Type of protection: IP20  
Art.-No. 2591409



### Tube fan

Multivent MV 100A 220-240V 50Hz 15W for space-saving installation in the tube. Connection for Ø100 mm. Can be used for supply or exhaust air.  
Nom. voltage: 230V, 50 Hz  
Delivery rate min./max:  
150/190 Vm<sup>3</sup>/h  
Type of protection: IP44  
Art.-No. 2591828



### Temperature sensor

Temperature sensor with integrated safety temperature limiter (STB). The mounting kit for a wall thickness of 40 to 90 mm includes a M20 x 1.5 mm cable gland, threaded sleeve, two O-rings and a flat gasket. Sensor type KTY81-110  
TF: 76°C + 0/-10°C  
Art.-No. 2558235  
(without cable)

## Temperature sensor



### Rod temperature sensor for bench heating or confined space conditions.

KTY81-110 for bench heating  
Length: 42 mm x Ø 6 mm  
Art.-No. 2557225  
(5m connection cable incl.)

### Blind temperature sensor

Blind stainless steel V4A for temperature sensor with Ø 6 mm metal sleeve. Approximately 35 mm outside diameter including grub screw for fixing the sensor element. Mounting hole of cabin lining 14 mm.  
Art.-No. 2591801

### Temperature sensor for sauna

Temperature sensor KTY81-110, STB Type SF139R, Temperature range 139° +/-2°C Ø55 mm Art.-No. 2595773



### Backflow flap

Made of galvanised sheet steel DN100 für Ø100 mm  
Art.-No. 2591829



### Electric regulator

1A 230V 50Hz for surface mounting. Speed controller, Continuously adjustable  
Art.-No. 2591827



# Spa Control Delta



## Technical data:

Condair Spa Control Delta Box		
Nominal power	Sauna	max. 9 kW
	Benchheating	1 kW
	Wallheating	1 kW
	Accessoires	1 kW
Dimensions (W x H x D)	353 x 353 x 107 mm	
Net weight	5,5 kg	
Control voltage	230 V	
Heating voltage	400 V	
Type of protection	IPX4	

Application	Variant
Steambath	standard
Steambath with benchheating	Benchheating
Caldarium	Bench and wallheating
Rasul	Bench and wallheating
Finnsauna	Finnsauna
Bio sauna for sauna heater with integrated steamer	Bio sauna (generator and Spa Control Delta)
Bio sauna for pure sauna heater, steam produced by ES4-2	Fin sauna
Dual cabin	Fin sauna

## Spa Control Delta

The innovative spa control for simultaneous control of steam bath, caldarium, rasul and different sauna variants such as bio and fin sauna.

It is possible to control various accessories such as light, fragrance, fan, freely configurable relay. It enables managing a steam bath and a fin sauna simultaneously and independently of each other with the same display. Operation is via a modern touch display, which is available in various versions.

Customisable display, you can upload your logo to appear on the screen.

## Advantages:

- The controller can control a steam bath and a sauna simultaneously and independently of each other.
- Easy switch between steam bath and sauna on the display.
- Flexible number of displays, one for both cabins or one for each cabin.
- Integrated web server where device settings can be managed.
- Smart Home connection via optional KNX gateway, Modbus integrated as standard.
- Keepwarm function saves energy

## Option:

Art.-No. 5250001: Spa Control Delta Standard  
Art.-No. 5250002: Spa Control Delta with benchheating  
Art.-No. 5250003: Spa Control Delta with bench- and wallheating for Rasul and Caldarium  
Art.-No. 5250004: Spa Control Delta for Finnsauna  
Art.-No. 5250005: Spa Control Delta for Bio sauna  
Art.-No. 2591666: Display cable shielded (50m)  
Art.-Nr. 2595463: Display cable shielded (per meter)

## Display cable, Pre-assembled with connectors

Art.-No. 2614137 Display cable Omega SPA compl. (1 m)  
Art.-No. 2614139 Display cable Omega SPA compl. (2 m)  
Art.-No. 2605756 Display cable Omega SPA compl. (6 m)  
Art.-No. 2614140 Display cable Omega SPA compl. (10 m)  
Art.-No. 2614141 Display cable Omega SPA compl. (15 m)

# Displays



## Omega Spa Display

Art.-No. 2591660: Display with flush-mounted housing  
Art.-No. 2591661: Display with surface-mounted housing

## Omega Spa Display, waterproof

Art.-No. 2600624: Display with flush-mounted housing, IPX7, SPA Control  
Art.-No. 2600626: Display with surface-mounted housing, IPX7, SPA C.

## AT4D Spa Display

Art.-Nr. 2604944: Display with flush-mounted housing  
Art.-Nr. 2604931: Display with surface-mounted housing

## AT4D Spa Display, waterproof

Art.-No. 2600627: UP housing (incl. mounting material), IPX7, AT4D  
Art.-No. 2600628: AP housing (incl. mounting material), IPX7, AT4D



## Display cable

Art.-No. 2591666: Display cable shielded (50 m)  
Art.-No. 2595463: Display cable shielded (per meter)

## Display cable, Pre-assembled with connectors

Art.-No. 2614137 Display cable Omega SPA compl. (1 m)  
Art.-No. 2614139 Display cable Omega SPA compl. (2 m)  
Art.-No. 2605756 Display cable Omega SPA compl. (6 m)  
Art.-No. 2614140 Display cable Omega SPA compl. (10 m)  
Art.-No. 2614141 Display cable Omega SPA compl. (15 m)

## Decoration panels to Omega und AT4D Spa Display

Art.-No. 2590183: Decoration panel steel  
Art.-No. 2590185: Decoration panel glass white  
Art.-No. 2590186: Decoration panel glass black

## Centring frame

Art.-No. 2590188: Centring frame & Seal. Only centring frame and sealing for usage of custom made decoration panel



## Gateway

for installation and operation of Modbus, KNX & Amazon Echo (Alexa) interfaces, Art.-No. 2595772)

## Remote Display for AT4D

Remote Display AT4D in plastic housing IP 65 (W 170 x H 280 x D 60 mm) for wall mounting. Version for flush-mounting not available anymore.

A three-inch grafic user interface provides easy access to important operating parameters such as temperature, lighting, cabin ventilation and fragrance injection. Remote control up to 8 generators. In hotels, health clubs and spa complexes, you have simple control of steam bath from reception or other remote site.

Art.-No. 2560646

## Connection cable must be ordered separately

Art.-No. 2591667: Clamps for shielding (5 pcs)

## Mounting sleeve for spots and push-buttons



### Good to know:



- Step 1: Find the correct mounting sleeve
- Step 2: Select warm white spot, coloured spot or steam bath button
- Step 3: Choose the correct length of the extension cable

### Mounting sleeve for coated GFK/Alu Surfaces:

Mounting hole 42 mm, mounting sleeve  $\varnothing 42 \times 110$  mm and nut, total length 113 mm (shortenable)  
Art.-No. 2591797

### Mounting sleeve for surfaces to be tiled:

For tiled wet rooms / steam baths  
Mounting hole 42 mm, mounting sleeve  $\varnothing 42 \times 110$  mm and nut, total length 113 mm (shortenable) with sealing flange and 6 screws for fixation  
Art.-No. 2591798



## LED-Spots and Piezo push button



### LED spot warm white

Built-in lamp VA chromed  
Type of protection: IP 65  
LED warm white 1 Watt  
Lense frosted  
Cover Ø60 mm  
Incl. connecting cable 20 cm  
Plug type: JST  
Art.-No. 2591804

### LED RGB Spot

Built-in lamp VA chromed  
Type of protection: IP 65  
LED-RGB 3x1 Watt  
Lense frosted  
Cover Ø60 mm  
Incl. connecting cable 20 cm  
Plug type: JST  
Art.-No. 2591806

### Push button red

Piezo push button with red ring illumination 24VDC  
Installed in holder/ cover screen innox.  
Chrome plated 60 mm outer diameter  
7 m wire 5 x 0.25 mm<sup>2</sup> with connector.  
For installation in mounting sleeve Ø42 mm  
Connection wire JST  
Art.-No. 2591795

### Push button blue

Piezo push button with blue ring illumination 24VDC  
Installed in holder/ cover screen innox.  
Chrome plated 60 mm outer diameter  
7m wire 5 x 0.25mm<sup>2</sup> with connector.  
For installation in mounting sleeve Ø42 mm  
Connection wire JST  
Art.-No. 2591796

### Extension cable for LED Spots

With plug and coupling JST 4 poles, colour code ( white )  
Art.-No. 2591814: Extension cable 1.0 m  
Art.-No. 2591815: Extension cable 1.5 m  
Art.-No. 2591816: Extension cable 2.5 m  
Art.-No. 2591817: Extension cable 5.0 m  
Art.-No. 2591818: Extension cable 7.0 m  
Art.-No. 2591819: Extension cable 15.0 m

### Specify desired length when ordering

Please order the fitting mounting sleeve

## LED Controller for RGB and warm white spots


### Technical data:

Electrical supply	230V/AC 50-60 Hz
Power supply	42VA/0.4 A
Operating temperature	0 to +50°C
Weight	1,5 kg
W x H x D	13 x 18 x 9 cm

### Good to know:

The settings of the lighting programs are made on the rotary switch. Optionally, it can be controlled with a 4-digit code.

If more than 10 spots are needed, the RGB control can be extended by a „slave“ module.



### Controller LED warm white

For max. 1-12 pcs. 1W spots. 1 x converter 350mA LCM-40 constant current.

Incl. poti for dimming on housing

Power supply cable 2m white, 230V/AC- 1,1A

7 m cable to spot 1 JST + end plug

Art.-No. 2591805

### Controller LED RGB

15 different light programmes can be chosen by a code switch

Synchronous colour gradient.

Dimmable via poti on housing

Output RGB-LED Spot 350 mA 1-10

Power supply 230 VAC with plug 230 VAC 1 Ph 50Hz 50W

7 m cable to spot 1 JST + end plug

Art.-No. 2591807

## Push button plates with flush-mountend housing

### Technical data push button plates:

Supply voltage	12- 24 VDC
Switching power	max. 1 Watt
Dimensions 1-fold push button plate	76 x 109 mm
Dimensions 2-fold push button plate	76 x 142 mm
Dimensions 3-fold push button plate	76 x 175 mm
Dimensions 4-fold push button plate	76 x 208 mm



### Technical data flush-mounted housing:

Dimensions housing for 1-fold push-button plate	96x129x52 mm (WxHxD)
Dimensions housing for 2-fold push-button plate	96x162x52 mm (WxHxD)
Dimensions housing for 3-fold push-button plate	96x195x52 mm (WxHxD)
Dimensions housing for 4-fold push-button plate	96x228x52 mm (WxHxD)



### Good to know:

Please remember to include a tube d25 for laying the push-button cable

### Push-button plates:

Dibond button plates with illuminated piezo push-button:  
Plates optionally with 1- 4 piezo buttons; blue ring  
illumination and indentation for name tags:  
7 m cable and screws M4x30

Art.-No. 2591799: Push-button plates 1-fold  
Art.-No. 2591800: Push-button plates 2-fold  
Art.-No. 2591808: Push-button plates 3-fold  
Art.-No. 2591809: Push-button plates 4-fold

### Push-button housing:

Flush-mounted housing for installing the push-button panels in building boards, dry- or masonry walls.  
Material: polystyrene (PS), black. Supplied with a protective cover made of EPS to define a clear tile edge and to protect against contamination of the interior.

Art.-No. 2591810: Housing 1-fold, Flush-mounted  
Art.-No. 2591811: Housing 2-fold, Flush-mounted  
Art.-No. 2591812: Housing 3-fold, Flush-mounted  
Art.-No. 2591813: Housing 4-fold, Flush-mounted

## Mounting material



**Connector pieces**  
stainless steel  
DS connector piece  
Ø30 to Ø22 mm  
Art.-No. 2591273

DS connector piece  
Ø35 to Ø30 mm  
Art.-No. 2591272

DS connector piece  
Ø45 to Ø22 mm  
Art.-No. 2549382

DS connector piece  
Ø45 to Ø35 mm  
Art.-No. 2591271

**Connector piece bow**  
Nickel-plated copper pipe  
with two clamps

Bow Ø22 mm  
Art.-No. 2402772

Bow Ø30 mm  
Art.-No. 2591252

Bow Ø35 mm  
Art.-No. 2402771

**Connector piece bow**  
Stainless steel  
Lieferung without clamps

Bow 90°/Ø45 mm/ R300 mm  
Art.-No. 2595900

Bow 90°/ Ø45 mm/ R66 mm  
Art.-No. 2591274

**Y- Hose connector piece**  
Stainless steel  
DS Y- Hose connector piece  
3 x Ø22 mm  
Art.-No. 1103447

DS Y- Hose connector piece  
3 x Ø30 mm  
Art.-No. 1101358

DS Y- Hose connector piece  
3 x Ø45 mm  
Art.-No. 1101164

DS Y- Hose connector piece  
1 x Ø45 mm 2 x Ø35 mm  
Art.-No. 2549383

**T-Piece**  
Copper tube nickel plated  
T-piece Ø22 mm  
Artikel No. 2402775

T-piece Ø30 mm  
Artikel No. 2402773

T-piece 1x Ø35/2x Ø22 mm  
Artikel No. 2402774

**Hose connection**  
Hose connection Ø22 mm  
Art.-No. 2553797

Hose connection Ø30 mm  
Art.-No. 2553893

Hose connection Ø35 mm  
Art.-No. 2402776

Hose connection Ø45 mm  
Art.-No. 2569589



#### Hose reduction

Hose reduction Ø35 to Ø22 mm  
Art.-No. 2401133



#### Condensate trap

Steam hose connection incl. condensate trap  
for ES4 and AT4D  
Art.-No. 2560515 for 5/8 kg/h  
Art.-No. 2560516 for 15kg/h  
Art.-No. 2560517 for 23/32kg/h  
Art.-No. 2560954 for 45/65kg/h



#### Condensate draining

Art.-No. 1118707 Condensate draining DS22 Ø22  
Art.-No. 2553793 Condensate draining DS35 Ø35  
Art.-No. 1118706 Condensate draining DS60 Ø30  
Art.-No. 1118705 Condensate draining DS80 Ø45



#### Funnel-Syphon

Funnel-Syphon SET Viega  
DN40  
Art.-No. 2595474



#### Condensate hose

Condensate hose KS10, 12/8 mm up to 50 m roll lenght.  
Specify desired length when ordering  
Art.-No. 1103350



#### Inlet Filter Z261

Art.-No. 1100416  
Fast closing block valve

#### Technical data:

Connections	Inlet/Outlet 3/8"i
Material	Filter frame brass
Housing	PA6
Fabric	Pa 6.6
Mesh size	125µ
Thread Ø	80µ

## Water treatment unit RO-H



### Water treatment units RO-H and RO-E:

Reverse osmosis (RO) is an effective and economic way of removing minerals from water. By removing the minerals from a humidifier's supply water, the limescale that builds up in the system is virtually eliminated. This results in a much lower level of required maintenance in all types of humidifier as well as in reduced energy consumption in steam humidifiers. For a steam capacity of up to 16 kg for the Condair Omega and up to 10 kg for the Condair Omega Pro, the RO-H system is suitable. For higher steam capacities there is the efficient Condair water treatment system RO-E.

### Water treatment unit RO-H

Voltage: AC 110-240, 50-60Hz, 75W  
Pure water output : 5°C 20l/h  
Max. pure water production: 1.0l/min  
Inlet water pressure: 0..6...3.5bar  
Water inlet temperature: 5–25 °C  
Salt retention rate: 95- 98 %  
Housing dimensions:  
Height: 470 mm, Width: 338 mm, Depth: 250 mm  
Art.-No. 2600217: Condair RO-HM

### Option:

Art.-No. 2600081: Filter set for water supply to RO-H  
Art.-No. 2600239: RO-H Leakage pan  
Art.-No. 2600083: External leakage sensor, set  
Art.-No. 2600257: RO-H armored hose set  
Art.-No. 2600230: Adjustable pressure reducer 1/2" BSF RBM 3bar

## Water treatment unit RO-E



RO-A with cover, please order separately

### Water treatment unit RO-E

Voltage and power:  
230V/1~/50...60Hz.

Pure water output at 5°C and 2 bar 58l/h

Pure water output at 15°C and 2 bar 98l/h

Water inlet pressure: 1,5- 6 bar

Water inlet temperature: 5- 20°C

Salt retention rate: 95- 98 %

Housing dimensions: (including cover)

Height: 792 mm, Width: 587 mm, Depth: 484 mm

Net weight: 54.0 kg



external Display

Art.-No. 5300002: Condair RO-E 40 EU

Art.-No. 5300008: Condair RO-E 40 CH

Art.-No. 5300011: Condair RO-E 40 UK

Art.-No. 5300014: Condair RO-E 40 UL

Other sizes on request

### Cover

Art.-No. 2606555: Cover Condair RO-E

### Options:

Art.-No. 2606708: External display (with 4m cable)


Art.-No. 2606419: Condair RO-E Leakage, Leak Sensor

Art.-No. 51514: Double filter unit 20"

Art.-No. 51497: SoftCab 25 DR water softener

Art.-No. 2606532: External Pure water tank 120 L

Art.-No. 8006: Salt briquettes 25kg



Condair Group AG  
Gwattstrasse 17, 8808 Pfäffikon/SZ  
Tel. +41 41 55 416 61 11  
ch.info@condair.com, www.condair.ch

Photos: Condair AG, Fotolia and Shutterstock

